


MX 11

Diritto maschio conico

Taper straight, male

Union simple mâle conique

Gerade Einschraubverschraubung, kegelig



Type	Ø Tubo	D1	D2	L1	L2	CH1	CH2	g Δ
11 04 18	4	R1/8	9	7,5	16,5	10	3	6,3
11 04 14	4	R1/4	9	11	20,5	14	3	16,1
11 06 18	6	R1/8	11,7	7,5	21	12	4	9,5
11 06 14	6	R1/4	12	11	20,5	14	4	14,3
11 08 18	8	R1/8	13,7	7,5	25	14	6	13,5
11 08 14	8	R1/4	13,7	11	23,5	14	6	14,4
new 11 08 38	8	R3/8	13,9	11,5	22,5	17	6	23,7
11 10 14	10	R1/4	15,7	11	30,5	16	8	20,3
11 10 38	10	R3/8	16	11,5	24	17	8	21,5
new 11 10 12	10	R1/2	15,7	14	27	22	8	-
11 12 38	12	R3/8	18,7	11,5	27,5	19	10	25,7
11 12 12	12	R1/2	19	14	27,5	22	10	42,1
new 11 12 14	12	R1/4	18,7	11	32	19	8	-
11 12 38	12	R3/8	18,7	11,5	27,5	19	10	25,7
11 12 12	12	R1/2	19	14	27,5	22	10	42,1


MX 12

Diritto maschio cilindrico

Parallel straight, male

Union simple mâle cylindrique

Gerade Einschraubverschraubung, zylindrisch



Type	Ø Tubo	D1	D2	D3	L1	L2	CH1	CH2	g Δ
12 04 M5	4	M5x0,8	9	8	4	19	9	-	4,9
12 04 18	4	G1/8	9	12,9	5	16,5	13	3	8,1
12 06 M5	6	M5x0,8	11,8	8	4	22,5	12	-	10,3
12 06 18	6	G1/8	11,7	12,9	5	19,5	13	4	9,5
12 06 14	6	G1/4	11,7	15,8	6,5	19,5	16	4	15,8
12 08 18	8	G1/8	13,7	12,9	5	23	14	6	12,8
12 08 14	8	G1/4	13,7	15,9	6,5	21,5	16	6	15,5
new 12 08 38	8	G3/8	13,7	20	7	21,5	17	6	-
12 10 14	10	G1/4	15,7	15,8	6,5	27,5	16	8	19,2
12 10 38	10	G3/8	16	20	7	25	17	8	24,4
new 12 10 12	10	G1/2	15,8	25	8,5	25,5	22	8	-
new 12 12 14	12	G1/4	18,8	16	6,5	28,5	19	8	-
12 12 38	12	G3/8	18,8	20	7	28	21	10	31,8
12 12 12	12	G1/2	18,8	25	8,5	26,5	22	10	41,8


MX 13

Diritto femmina

Female straight

Union simple femelle

Gerade Aufsraubverschraubung



Type	Ø Tubo	D1	D2	L1	L2	CH	g Δ
13 04 18	4	G1/8	9	7	24,5	13	-
13 06 18	6	G1/8	12	7	26,5	13	-
13 06 14	6	G1/4	12	10	31	16	-
13 08 18	8	G1/8	13,8	7	26,5	14	18,2
13 08 14	8	G1/4	14	10	31	16	-
13 08 38	8	G3/8	14	11	32,5	21	-
13 10 14	10	G1/4	15,7	10	33	16	24
13 10 38	10	G3/8	16	11	34,5	21	-
13 10 12	10	G1/2	16	11	36	24	-
13 12 38	12	G3/8	19	11	35,5	21	77,5
13 12 12	12	G1/2	19	11	37	24	-


MX 14

Gomito maschio conico

Taper elbow fitting, male

Raccord à coude mâle conique

Winkerverschraubung, kegelig



Type	Ø Tubo	D1	D2	L1	L2	L3	g Δ
14 04 18	4	R1/8	9	9,8	17	17,5	10,2
14 06 18	6	R1/8	12	9,8	17	20,5	14
14 06 14	6	R1/4	12	11,3	20,7	20,5	20,8
14 08 18	8	R1/8	14	9,5	18	22,5	19,6
14 08 14	8	R1/4	14	11,3	20,7	22,5	22,3
14 10 14	10	R1/4	16	12,1	21,5	24,5	39,5