


MX 11

Diritto maschio conico

Taper Stud, male

Union simple, conique

Gerade Einschraubverschraubung, kegelig



| Tipo | Øe Tubo | D1 | D2 | L1 | L2 | CH1 | CH2 | g Δ |
|----------|---------|------|----|------|------|-----|-----|------------|
| 11 04 18 | 4 | R1/8 | 9 | 7,5 | 15,5 | 10 | 3 | 6 |
| 11 04 14 | 4 | R1/4 | 9 | 11 | 20 | 14 | 3 | 16 |
| 11 06 18 | 6 | R1/8 | 12 | 7,5 | 20,5 | 12 | 4 | 9,5 |
| 11 06 14 | 6 | R1/4 | 12 | 11 | 20 | 14 | 4 | 14 |
| 11 08 18 | 8 | R1/8 | 14 | 7,5 | 24,5 | 14 | 6 | 13,5 |
| 11 08 14 | 8 | R1/4 | 14 | 11 | 23 | 14 | 6 | 15 |
| 11 10 14 | 10 | R1/4 | 16 | 11 | 30 | 16 | 8 | 20 |
| 11 10 38 | 10 | R3/8 | 16 | 11,5 | 23,5 | 17 | 8 | 21 |
| 11 12 38 | 12 | R3/8 | 18 | 11,5 | 27 | 18 | 10 | 26 |
| 11 12 12 | 12 | R1/2 | 18 | 14 | 27 | 22 | 10 | 42 |


MX 12

Diritto maschio cilindrico

Parallel Stud, male

Union simple male cylindrique

Gerade Einschraubverschraubung, zylindrisch



| Tipo | Øe Tubo | D1 | D2 | D3 | L1 | L2 | CH1 | CH2 | g Δ |
|----------|---------|--------|----|----|-----|------|-----|-----|------------|
| 12 04 M5 | 4 | M5x0,8 | 9 | 8 | 4 | 19 | 9 | - | 5 |
| 12 04 18 | 4 | G1/8 | 9 | 13 | 5 | 16 | 13 | 3 | 8 |
| 12 06 18 | 6 | G1/8 | 12 | 13 | 5 | 19 | 13 | 4 | 10 |
| 12 06 14 | 6 | G1/4 | 12 | 16 | 6,5 | 18,5 | 16 | 4 | 16 |
| 12 08 18 | 8 | G1/8 | 14 | 13 | 5 | 22,5 | 14 | 6 | 13 |
| 12 08 14 | 8 | G1/4 | 14 | 16 | 6,5 | 21 | 16 | 6 | 15,5 |


MX 14

Gomito maschio conico

Taper Elbow, male

Raccord à coude mâle conique

Winkelverschraubung, kegelig



| Tipo | Øe Tubo | D1 | D2 | L1 | L2 | L3 | g Δ |
|----------|---------|------|----|-----|----|----|------------|
| 14 04 18 | 4 | R1/8 | 9 | 7,5 | 16 | 17 | 10 |
| 14 06 18 | 6 | R1/8 | 12 | 7,5 | 16 | 20 | 14 |
| 14 06 14 | 6 | R1/4 | 12 | 11 | 20 | 20 | 21 |
| 14 08 18 | 8 | R1/8 | 14 | 7,5 | 17 | 21 | 19 |
| 14 08 14 | 8 | R1/4 | 14 | 11 | 20 | 21 | 23 |


MX 15

Gomito maschio conico girevole

Taper Swivelling Elbow, male

Raccord à coude tournant, mâle conique

Schwenkbare Winkelverschraubung, kegelig



| Tipo | Øe Tubo | D1 | D2 | L1 | L2 | L3 | CH | g Δ |
|----------|---------|------|----|------|------|------|----|------------|
| 15 04 18 | 4 | R1/8 | 9 | 7,5 | 17,5 | 17 | 10 | 11 |
| 15 06 18 | 6 | R1/8 | 12 | 7,5 | 20 | 21,5 | 13 | 21 |
| 15 06 14 | 6 | R1/4 | 12 | 11 | 24 | 21,5 | 14 | 25 |
| 15 08 18 | 8 | R1/8 | 14 | 7,5 | 20 | 22 | 13 | 22 |
| 15 08 14 | 8 | R1/4 | 14 | 11 | 24 | 22 | 14 | 26 |
| 15 10 14 | 10 | R1/4 | 16 | 11 | 26,5 | 25,5 | 16 | 37 |
| 15 10 38 | 10 | R3/8 | 16 | 11,5 | 27 | 25,5 | 17 | 39 |
| 15 12 38 | 12 | R3/8 | 18 | 11,5 | 30,5 | 28 | 21 | 65 |
| 15 12 12 | 12 | R1/2 | 18 | 14 | 33,5 | 28 | 22 | 65 |