

ANALOGIC TIMER TIMER ANALOGICO



M8/M9/M12/M23

EN175301-803

EXTENSIONS
PROLUNGHE

FUSE HOLDERS
PORTAFUSIBILI

AUTOMOTIVE

M8/M12
DISTRIBUTION
BOXES
SCATOLE DI
DISTRIBUZIONE
M8/M12

7/8"

MIL-C5015 style
CONNECTORS
CONNETTORI
SERIE MIL-C5015

INDUSTRIAL
CONNECTORS
CONNETTORI
INDUSTRIALI

EN 175 000

ACCESSORIES
ACCESSORI

SENSOR
SWITCHES
SENSORI

112

PRODUCT DESCRIPTION

Timer for DIN 43650 connectors

Type of contact: female

Number of contacts: 2 poles + earth

Standard: IEC 61076-2-101 (Ed. 1)/ IEC 60947-5-2

Housing Color: black

TECHNICAL DATA

Rated voltage: 24 - 240V AC/DC ± 10% 50/60 Hz

Rated current: 1 A

Current consumption: 4 mA max

Connection: DIN 43650-A/ISO 4400

Off time: 0,5-45 min

On time: 1,5 -30 sec

Scale accuracy: ± 10%

Indicators: red Led - on phase / red Led - off phase

MATERIALS

Housing material: Nylon 6 + 30% Glass fibre

ENVIRONMENTAL CONDITIONS

Protection class (IEC 60529): IP 65

Temperature range: -40°C to +60°C

PACKAGING

Carton box (1 piece)

DESCRIZIONE PRODOTTO

Timer per connettore DIN 43650

Tipo di contatto: femmina

Numero contatti: 2 poli + terra

Standard: IEC 61076-2-101 (Ed. 1)/ IEC 60947-5-2

Colore custodia: nera

DATI TECNICI

Tensione Oper: 24 - 240V AC/DC ± 10% 50/60 Hz

Corrente operativa: 1 A

Corrente assorbita: 4 mA max

Connessione: DIN 43650-A/ISO 4400

Tempo di pausa: 0,5-45 min

Tempo di lavoro: 1,5 -30 sec

Precisione: ± 10%

Indicatori: Led rosso-fase on/Led rosso-fase off

MATERIALI

Materiale custodia: Nylon 6 + 30% fibra di vetro

CONDIZIONI AMBIENTALI

Grado di protezione (IEC 60529): IP 65

Range di temperatura: -40°C to +60°C

IMBALLAGGIO:

Scatola di cartone (1 pezzo)

DIGITAL TI



IER DIGITALE

PRODUCT DESCRIPTION

Timer for DIN 43650 connectors

Housing Color: black

TECHNICAL DATA

Rated voltage: 24...240V AC/DC

Rated current: 1 A

Current consumption: 4 mA max

Connection: DIN 43650-A/ISO 4400

Off time: From 0min to 9.5min., step 0.5min.

From 10min. to 99min., step 1min.

On time: From 0s.-9.5 s., step 0.5 s.

From 10s. to 99s., step 1s.

Repeat accuracy: ± 0.01%

Indicators: GREEN LED: OFF phase - RED LED: ON phase

MATERIALS

Housing material: ABS V0

ENVIRONMENTAL CONDITIONS

Protection class IP65 assembled

DESCRIZIONE PRODOTTO

Timer per connettore DIN 43650

Colore custodia: nera

DATI TECNICI

Tensione Oper: 24...240V AC/DC

Corrente operativa: 1 A

Corrente assorbita: 4 mA max

Connessione: DIN 43650-A/ISO 4400

Tempo di pausa: From 0min to 9.5min., step 0.5min.

From 10min. to 99min., step 1min.

Tempo di lavoro: From 0s.-9.5s., step 0.5 s.

From 10s. to 99s., step 1s.

Precisione: ± 0.01%

Indicatori: GREEN LED: OFF phase - RED LED: ON phase

MATERIALI

Materiale custodia: ABS V0

CONDIZIONI AMBIENTALI

Grado di protezione IP65 assemblaggio