

CHARACTERISTICS

Ambient temperature	-10 ÷ +45 °C
Fluid	10 µm filtered air
Commutation system	spool system
Pressure Max	10 bar
Connections	M5, for sub-base
Nominal bore (mm)	2
Nominal flow rate (NI/min)	150
Valve body	zamak
Seals	NBR
Electropilot/Coil	A series/U05
Voltage	24 V DC - 12 V DC - 24 V AC - 110 V AC - 230 V AC



CODIFICATION KEY

E	-	0	2	2	4
1		2	3	4	

1 Series	2 Type	3 Control 14	4 Return 12
E = COMPA 2 Miniature valves	02 = 5/2 Sub-base mounting 04 = 5/2 Threaded body M5 05 = 5/3 c.c. Sub-base mounting 06 = 5/3 o.c. Sub-base mounting 07 = 5/3 p.c. Sub-base mounting 08 = 5/3 c.c. Threaded body M5 09 = 5/3 o.c. Threaded body M5 10 = 5/3 p.c. Threaded body M5	2 = Electrical DC 4 = Pneumatic 7 = Electrical DC/AC	0 = Pneumomechanical spring 2 = Electrical DC 4 = Pneumatic impulse 7 = Electrical DC/AC

o.c. = open centres c.c. = closed centres p.c. = pressurized centres

Pneumatic impulse

<p>■ Single impulse</p> <p style="text-align: right;">E-0240</p>	<p>■ Double impulse</p> <p style="text-align: right;">E-0244</p>
--	--

Electrical impulse

<p>■ Single impulse</p> <p style="text-align: right;">E-0220 E-0270</p>	<p>■ Double impulse</p> <p style="text-align: right;">E-0222 E-0277 E-0522 E-0622 E-0722</p>
---	--

Inlet plate G1/8


Manifold sub-base, side connections M5




Solenoid valves are supplied without coil and connector

Pneumatic impulse - 5/2 Valves M5

■ Single impulse




■ Double impulse




Electrical impulse - 5/2 Valves M5

■ Single impulse





■ Double impulse



Electrical impulse - 5/3 Valves M5





















































■ Double impulse



DIN C (8 mm)

For further information please contact our Sales Office.

5/2 Valves M5 - Mechanical and manual operation

<p>■ Lever valve</p>   <p>LEVER E-15422G ■ YELLOW E-15422N ■ BLACK E-15422R ■ RED</p>			<p>■ Push-pull valve</p>   <p>E-15420 E-15420A</p>			<p>■ Ball push valve</p>   <p>E-15402A</p>									
<p>■ Ball push valve for mechanical screw operation</p>   <p>E-15403A</p>				<p>■ Ball push valve for mechanical panel operation</p>   <p>E-15412A</p>											
 AI-3550	 AI-3551	 AI-3560	 AI-3562	 AI-3563	 AI-3570	 AI-3571	 AI-3572	 AI-3511Q ■	 AI-3514Q ■	 AI-3515Q ■	 AI-3520Q ■	 AI-3524Q ■	 AI-3522Q ■	 AI-3525Q ■	 AI-3526Q ■
 AI-3512Q ■	 AI-3516Q ■	 AI-3517Q ■	 AI-3521Q ■	 AI-3513Q ■	 AI-3514QD ■	 AI-3519Q ■	 AI-3516QD ■	 AI-3523Q ■							
 AI-3511 ■	 AI-3514 ■	 AI-3515 ■	 AI-3520 ■	 AI-3522 ■	 AI-3524 ■	 AI-3525 ■	 AI-3526 ■								
 AI-3512 ■	 AI-3516 ■	 AI-3517 ■	 AI-3521 ■	 AI-3523 ■											
 AI-3513 ■	 AI-3514D ■	 AI-3519 ■													
 AI-3516D ■															

Solenoid valves are supplied without coil and connector