


OX 10

Dado

Nut

Écrou

Überwurfmutter



Tipo	Ø Tubo	D1	L1	CH	g Δ
10 00 04	4	M8x1	11	10	4,3
10 00 06	6	M10x1	11,5	12	5,62
10 00 08	8	M12x1	12	14	7,1
10 00 10	10	M16x1,5	15,5	19	18,35
10 00 12	12	M18x1,5	15,5	22	25,78


OX 11

Diritto maschio conico

Taper Straight, male

Union Simple mâle conique

Gerade Einschraubverschraubung, kegelig



Tipo	Ø Tubo	D1	L1	L2	CH1	CH2	g Δ
11 04 18	4	R1/8	8	27	10	10	12,93
11 06 18	6	R1/8	8	27	11	12	14,85
11 06 14	6	R1/4	11	31	14	12	23,96
11 08 18	8	R1/8	8	29	12	14	17,52
11 08 14	8	R1/4	11	32	14	14	25
11 10 14	10	R1/4	11	35,5	17	19	42,42
11 10 38	10	R3/8	11,5	37	17	19	51,19
11 12 38	12	R3/8	11,5	37	19	22	59,26
11 12 12	12	R1/2	14	40,5	22	22	81,12


OX 13

Diritto femmina

Female Straight

Union simple femelle

Gerade Aufschraubverschraubung



Tipo	Ø Tubo	D1	L1	L2	CH1	CH2	g Δ
13 06 18	6	G1/8	8,5	28	14	12	20,53
13 08 14	8	G1/4	10,5	31	19	14	-
13 10 14	10	G1/4	10,5	34,5	19	19	-
13 10 38	10	G3/8	10,5	36,5	22	19	-
13 12 38	12	G3/8	10,5	36,5	22	22	-
13 12 12	12	G1/2	12,5	37,5	24	22	69,19


OX 14

Gomito maschio conico

Taper Elbow Fitting, male

Raccord à coude mâle conique

Winkelverschraubung, kegelig



Tipo	Ø Tubo	D1	L1	L2	L3	CH1	CH2	g Δ
14 04 18	4	R1/8	6,5	17	23	10	10	16,66
14 06 18	6	R1/8	6,5	17	24	10	12	19,17
14 06 14	6	R1/4	10	21,5	24	10	12	21,91
14 08 14	8	R1/4	10	21,5	24,5	10	14	23,06
14 10 14	10	R1/4	12,5	24,5	30,5	12	19	46,81
14 10 38	10	R3/8	11,5	24,5	30,5	12	19	49,82
14 12 38	12	R3/8	12,5	25,5	33	17	22	72,46
14 12 12	12	R1/2	13,5	30	35	19	22	91,15